Keizou BABA, S.N. 09/448,885
Page 2

Dkt. 2271/60735

Listing of Claims

The following listing of claims will replace all prior versions, and listings, of claims in the subject application:

1. (original) A facsimile monitoring system comprising:

a facsimile having an interface which can be connected with a personal computer; and

a personal computer connected with the facsimile and including monitoring software for monitoring a state of a memory transmission file of the facsimile,

wherein, when a memory transmission by the facsimile is completed, a message of a completion thereof is displayed on a displaying panel of said personal computer immediately thereafter.

2. (original) A facsimile monitoring system comprising:

a facsimile having an interface which can be connected with a personal computer; and

a personal computer connected with the facsimile and including monitoring software for monitoring a state of a memory transmission file of said facsimile,

wherein, when there exists a communication error by the facsimile a message of an alarm is displayed on a displaying panel of said personal computer immediately thereafter.

3. (original) A facsimile monitoring system comprising:

a facsimile device having an interface which can be connected with a personal computer; and

a personal computer connected with the facsimile and including monitoring a state of a

Keizou BABA, S.N. 09/448,885   Dkt. 2271/60735
Page 3

memory transmission file of said facsimile device,

wherein, when there exists a file in said facsimile device indicating a communication

error, said file of communication error can be deleted using said personal computer.

4. (original) A facsimile monitoring system comprising:

a facsimile device having an interface which can be connected with a personal computer;
and

a personal computer connected with the facsimile device and including monitoring
software for monitoring a state of a memory transmission file of said facsimile device,

wherein, when there exists a file in said facsimile device indicating a communication

error, an address of said communication error file and a transmission property thereof can be

changed from said personal computer.

5. (original) A facsimile monitoring system comprising:

a facsimile device having an interface which can be connected with a personal computer;
and

a personal computer connected with the facsimile and including monitoring software for

monitoring a state of a memory transmission file of said facsimile device,

wherein, when there exists a file in said facsimile device indicating a communication

error, at least one of an address of said communication error file and a transmission property

thereof can be changed from said personal computer.

6. (currently amended) A method of monitoring a facsimile device from a personal

Keizou BABA, S.N. 09/448,885   Dkt. 2271/60735
Page 4

computer comprising the steps of:

   monitoring a state of a memory transmission of said facsimile device; and

   displaying a message of a completion of the memory transmission on a display of a the

personal computer connected to the facsimile device, immediately after the memory transmission

is completed.

   7. (currently amended) A method of monitoring a facsimile device from a personal

computer comprising the steps of:

   monitoring a state of a memory transmission file of said facsimile; and

   displaying an error message indicating a communication error in the memory transmission

on a display of a the personal computer connected to the facsimile device, immediately after the

communication error occurs.

   8. (original) A method of monitoring a facsimile device comprising the steps of:

   monitoring a state of a memory transmission file of said facsimile device; and

   deleting a file indicating a communication error in said facsimile device from a personal

computer, when there exists a file indicating the communication error.

   9. (original) A method of monitoring a facsimile device comprising the steps of:

   monitoring a state of a memory transmission of said facsimile device; and

   changing an address in a communication error file and a transmission property thereof

from a personal computer, when there exists the communication error file.

Keizou BABA, S.N. 09/448,885   Dkt. 2271/60735
Page 5

10. (currently amended) A method of monitoring a facsimile device comprising the steps

of:

monitoring a state of a memory transmission of said facsimile device; and

changing at least one of an address in a communication error file and a transmission

property thereof from a personal computer, when there exists the communication error file.

11. (currently amended) A facsimile device monitoring system for monitoring a

communication result of a facsimile device from an external terminal, comprising:

a facsimile device provided with a result sending out medium sending out a

communication result to an interface through which an external terminal can obtain information

regarding a state of a memory transmission file of said facsimile device; and

an external terminal provided with

a display medium displaying and outputting the communication result sent from

said facsimile device, and

a result monitoring medium executing adapted to execute an operation of

monitoring the communication result from said result sending out medium a state of a memory

transmission file of said facsimile device and causing said communication the monitoring result

to be displayed on said display medium of said external terminal immediately thereafter

promptly.

12. (original) The facsimile device monitoring system as defined in claim 11,

wherein said result monitoring medium monitors a state of a memory transmission file of

said facsimile device, and

Keizou BABA, S.N. 09/448,885   Dkt. 2271/60735
Page 6

wherein said result monitoring medium sends out a completion result or an error result of

the memory transmission to said external terminal, and

wherein said external terminal outputs a completion message or an alarm message as a

completion result or an error result.

13. (original) The facsimile device monitoring system as defined in claim 11,

wherein said external terminal is provided with an indication medium for designating a

transmission file to be held in memory of said facsimile device and for indicating treatment of

said transmission file, and further comprising:

a file treatment medium for treating the file in the memory of said facsimile device on a

basis of the indication from said indication medium.

14. (original) The facsimile device monitoring system as defined in claim 12,

wherein said external terminal is provided with an indication medium designating the

transmission file to be held in a memory of said facsimile device and indicating a treatment of

said transmission file, and further comprising:

a file treatment medium for treating the file in the memory of said facsimile device on the

basis of the indication from said indication medium.

15. (original) The facsimile device monitoring system as defined in claim 13,

wherein said file treatment medium deletes a transmission error file designated on a basis

of the indication transmitted by said indication medium, from the memory of said facsimile

device.

Keizou BABA, S.N. 09/448,885   Dkt. 2271/60735
Page 7

16. (original) The facsimile device monitoring system as defined in claim 14,

wherein said file treatment medium deletes a transmission error file designated on a basis

of the indication transmitted by said indication medium from the memory of said facsimile

device.

17. (original) The facsimile device monitoring system as defined in claim 14,

wherein said file treatment medium deletes a transmission error file designated on a basis

of the indication transmitted by said indication medium from the memory of said facsimile

device.

18. (previously presented) The facsimile device monitoring system as defined in claim

14,

wherein said file treatment medium changes one or more of an address of the designated

transmission error file and a transmission property.